

| 2015 MIRAGE | | TECHNICAL AND MECHANICAL FEATURES | | |
|---------------------------------|--|--|--|--|
| Feature Description | | DE | RF | ES |
| Engine | | | | |
| Type | | 1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder | 1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder | 1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder |
| Engine Code | | 3A92 | 3A92 | 3A92 |
| Materials | | Aluminum Head/ Aluminum Block | Aluminum Head/ Aluminum Block | Aluminum Head/ Aluminum Block |
| Bore x Stroke | | 75.0mm x 90.0mm | 75.0mm x 90.0mm | 75.0mm x 90.0mm |
| Compression Ratio | | 10.5:1 | 10.5:1 | 10.5:1 |
| Displacement | | 1193cc | 1193cc | 1193cc |
| Horsepower | | 74 @ 6000 rpm | 74 @ 6000 rpm | 74 @ 6000 rpm |
| Torque | | 74 lb-ft @ 4000 rpm | 74 lb-ft @ 4000 rpm | 74 lb-ft @ 4000 rpm |
| Fuel System | | ECI-MULTI | ECI-MULTI | ECI-MULTI |
| Transmission | | | | |
| 5 Speed Manual Transmission | | STD | - | STD |
| 1st | | 3.545 | - | 3.545 |
| 2nd | | 1.913 | - | 1.913 |
| 3rd | | 1.31 | - | 1.31 |
| 4th | | 0.973 | - | 0.973 |
| 5th | | 0.804 | - | 0.804 |
| Reverse | | 3.214 | - | 3.214 |
| Final Drive | | 4.055 | - | 4.055 |
| INVEC-III CVT | | OPT | STD | OPT |
| CVT Automatic Ratios | | 4.007 - 0.550 | 4.007 - 0.550 | 4.007 - 0.550 |
| Reverse | | 3.771 | 3.771 | 3.771 |
| Final Drive | | 3.757 | 3.757 | 3.757 |
| Suspension | | | | |
| Front | | MacPherson type strut | MacPherson type strut | MacPherson type strut |
| Rear | | Torsion Beam | Torsion Beam | Torsion Beam |
| Steering | | | | |
| Type | | Rack-and-pinion, Electric Power Assist | Rack-and-pinion, Electric Power Assist | Rack-and-pinion, Electric Power Assist |
| Turn Circle - Curb to Curb (ft) | | 30.2 ft. | 30.2 ft. | 30.2 ft. |
| Turn Circle - Wall to Wall (ft) | | 32.1 ft. | 32.1 ft. | 32.1 ft. |
| Brakes/ Tires/ Wheels | | | | |
| Front | | Ventilated disc | Ventilated disc | Ventilated disc |
| Rear | | Drum Brake | Drum Brake | Drum Brake |
| Anti-Lock Brakes | | STD | STD | STD |
| Wheels | | 14in steel wheels with covers | 14in alloy wheels | 14in alloy wheels |
| Tires | | 165/65R14 | 165/65R14 | 165/65R14 |
| Spare Tire (Temporary Tire) | | STD | STD | STD |
| Exterior Dimensions | | | | |
| Wheelbase | | 96.5 in. | 96.5 in. | 96.5 in. |
| Length | | 148.8 in. | 148.8 in. | 148.8 in. |
| Width | | 65.6 in. | 65.6 in. | 65.6 in. |
| Height | | 59.4 in. | 59.4 in. | 59.4 in. |
| Track, Front | | 56.3 in. | 56.3 in. | 56.3 in. |
| Track, Rear | | 55.7 in. | 55.7 in. | 55.7 in. |
| Min. Ground Clearance | | 6.3 in. | 6.3 in. | 6.3 in. |

| 2015 MIRAGE | | TECHNICAL AND MECHANICAL FEATURES | | |
|---|--|-----------------------------------|---------------------------|---------------------------|
| Feature Description | | DE | RF | ES |
| Interior Dimensions | | | | |
| Head Room | | | | |
| Front Head Room | | 39.1 in. | 39.1 in. | 39.1 in. |
| Rear Head Room | | 37.3 in. | 37.3 in. | 37.3 in. |
| Leg room | | | | |
| Front Leg Room | | 41.7 in. | 41.7 in. | 41.7 in. |
| Rear Leg Room | | 34.0 in. | 34.0 in. | 34.0 in. |
| Shoulder room | | | | |
| Front Shoulder Room | | 51.7 in. | 51.7 in. | 51.7 in. |
| Rear Shoulder Room | | 51.0 in. | 51.0 in. | 51.0 in. |
| Hip room | | | | |
| Front Hip Room | | 48.9 in. | 48.9 in. | 48.9 in. |
| Rear Hip Room | | 49.0 in. | 49.0 in. | 49.0 in. |
| SAE volume | | | | |
| Interior Volume | | 103.3 cu.ft. | 103.3 cu.ft. | 103.3 cu.ft. |
| Passenger Volume | | 86.1 cu.ft. | 86.1 cu.ft. | 86.1 cu.ft. |
| Cargo volume (rear seats up) | | 17.2 cu.ft. | 17.2 cu.ft. | 17.2 cu.ft. |
| Cargo volume (rear seats down) | | 47.0 cu.ft. | 47.0 cu.ft. | 47.0 cu.ft. |
| Capacities | | | | |
| Passenger Seating Capacity | | 5 | 5 | 5 |
| Fuel Tank Capacity | | 9.2 gal | 9.2 gal | 9.2 gal |
| Weights | | | | |
| GVWR CVT (5MT) | | 3,020 lbs (2,910 lbs) | 3,020 lbs | 3,020 lbs (2,910 lbs) |
| Curb Weight CVT (5MT) | | 2,029 lbs (1,973 lbs) | 2,029 lbs | 2,051 lbs (1,996 lbs) |
| Fuel Economy | | | | |
| City (MT) | | 37 (34) | 37 | 37 (34) |
| Highway (MT) | | 44 (42) | 44 | 44 (42) |
| Combined (MT) | | 40 (37) | 40 | 40 (37) |
| Electrical | | | | |
| Battery | | 55D23L | 55D23L | 55D23L |
| Alternator (Amps) | | 85Amps | 85Amps | 85Amps |
| Warranties | | | | |
| Basic | | 5 years or 60,000 miles | 5 years or 60,000 miles | 5 years or 60,000 miles |
| Powertrain | | 10 years or 100,000 miles | 10 years or 100,000 miles | 10 years or 100,000 miles |
| Anti-corrosion | | 7 years or 100,000 miles | 7 years or 100,000 miles | 7 years or 100,000 miles |
| Roadside Assistance | | STD | STD | STD |
| Updated 7/24/2015 Information subject to change without notice | | | | |